



DELMHORST
EUROPE
WHEN ACCURACY IS THE POINT.[™]
**F-2000 digital
moisture meter hay**



The F-2000 is great for hay producers looking to enhance quality control.

The F-2000 checks hay moisture in the windrow or in bales, and comes with the same accuracy and clarity as the FX-2000.

Your Benefits:



- Bright, clear digital display
- Averages up to 100 accumulated readings
- Displays average and highest of accumulated readings
- Moisture Range: 6%-40% on hay
- Built-in calibration check
- Audible, adjustable alarm alerts you when a pre-selected MC has been reached
- Operating Temperature: from 0°C to 50°C
- Size: 20x8x4cm (8x3x1½")
- Weight: 285gr. (10 oz)
- Rugged construction ensures years of reliable use
- Optional sturdy plastic carrying case
- 9V battery
- 3-year warranty

Special Packages:

Moisture meter F-2000 Value Package:

Includes meter and 1235 25cm (10") pen electrode

Moisture meter F-2000 Deluxe Package:

Includes meter, H-4 handle, 830-2 25cm (10") pen electrode, 831 windrow probe, and carrying case.

Moisture meter F-2000 Deluxe 18 Package:

Includes meter, H-4 handle, 830-3 45cm (18") pen electrode, 831 windrow electrode and carrying case



Available electrodes:



1235

Pen electrode available in 2 lengths:

1235 - 25cm (10")
1235/18 - 45cm (18")

(Attaches directly to the connector on top of the meter)

For moisture measuring in standard bales



830-X

Pen electrode available in different lengths:

830-2 - 25cm (10")
830-3 - 45cm (18")
830-4 - 90cm (36")

(Requires H-4 Handle)

For moisture measuring in standard and high density bales



831

Short needle electrode (requires H-4 Handle)

For testing MC of hay in the windrow



H-4

Handle for electrodes 830-x and 831.

Two handed operation is recommended over using an electrode that connects directly to the top of the meter (like our 1235 series) to minimize stress placed on the meter casing.



MCS-4

This moisture content standard is great for verifying that your F-series moisture meter is in calibration. With two electrical resistance values (16% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.