

**HT-3000**  
**Thermo-hygro meter**



The HT-3000 thermo-hygrometer is a great tool for monitoring the level of humidity during restoration projects. With a simple interface, fast acclimation, and useful statistics like dew point and grains per pound, the HT-3000 is a great value at an economical price. Use the HT-3000 in conjunction with one of our moisture meters for a thorough assessment of every job.

**Your Benefits:**

- Bright, clear digital display
- Relative Humidity Range: 0% - 100%, sensor can be used for in-situ concrete testing following the ASTM F170 standard
- Temperature Range: -40°C - 124°C (-40°F - 255°F)
- Dew Point Range: -40°C - 80°C (-40°F - 176°F)
- GPP Range: 0.1 - 3820 GPP (Grains Per Pound)
- GPK Range: 0.01 - 545 GPK (Grains Per Kilogram)
- Vapor Pressure Range: 0 - 7 PSI (Pounds Per Square Inch)
- Vapor Pressure Range: 0 - 47 KPA (Kilopascals)
- Built-in back-light makes reading in dark places a cinch
- Auto shut-off timer saves battery life
- Reading HOLD Feature
- Size: 22x9x4,5cm (8 ½" x 3 3/8" x 1 ¾")
- Weight: 312gr. (11 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty



**Electrodes & Accessories:**

No need for additional electrodes or accessories. The HT-3000 is ready to use and packed in a sturdy carrying case.

**Optional assisting moisture meters:**

