

**HT-4000**  
**Thermo-hygro meter**



For restoration projects, a thermo-hygrometer may assist you in combination with a separate moisture meter. **The HT-4000**, a fast response stand-alone thermo-hygrometer has the same fast acclimating RH/T sensor found in our popular TotalCheck and Navigator Pro 3-in-1 moisture meters.

**Your Benefits:**



- Bright, clear digital display
- Relative Humidity Range: 0% - 100%, sensor can be used for in-situ concrete testing following the ASTM F170 standard
- Temperature Range: -40°C - 124°C (-40°F - 255°F)
- Dew Point Range: -40°C - 80°C (-40°F - 176°F)
- GPP Range: 0.1 - 3820 GPP (Grains Per Pound)
- GPK Range: 0.01 - 545 GPK (Grains Per Kilogram)
- Vapor Pressure Range: 0 - 7 PSI (Pounds Per Square Inch)
- Vapor Pressure Range: 0 - 47 KPA (Kilopascals)
- Built-in back-light makes reading in dark places a cinch
- Auto shut-off timer saves battery life
- Reading HOLD Feature
- Size: 22x9x4,5cm (8 ½" x 3 3/8" x 1 ¾")
- Weight: 312gr. (11 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty

**Recommended available Accessories:**



**RH/T-S1**

Detachable relative humidity/temperature sensor that is included with Total Check and HT-4000F.

Can be used to obtain ambient RH/T readings, or for performing tests on concrete.

**RH/T-S3:**

Can be used to perform tests on concrete according ASTM F-2170 norm.



**RH/T-C1**

Extension cable, connects to the RH/T-S sensor, allowing you to easily view your meter's screen while performing tests on concrete.