



The Delmhorst is proud to present the HT-4000, a stand-alone thermo-hygrometer for flooring installers and restoration contractors alike. The HT-4000 has the same fast acclimating RH/T sensor found in our popular TotalCheck and Navigator Pro 3-in-1 moisture meters. For contractors who prefer having separate meters to one combination meter, the HT-4000 is the perfect solution. The meter's sensor is also detachable, making the HT-4000 ideal for testing a concrete slab (if needed, even according to the ASTM F2170 standard).

Your Benefits:



- Bright, clear digital display
- Relative Humidity Range: 0% - 100%, sensor can be used for in-situ concrete testing following the ASTM F170 standard
- Temperature Range: -40°C - 124°C (-40°F - 255°F)
- Dew Point Range: -40°C - 80°C (-40°F - 176°F)
- GPP Range: 0.1 - 3820 GPP (Grains Per Pound)
- GPK Range: 0.01 - 545 GPK (Grains Per Kilogram)
- Vapor Pressure Range: 0 - 7 PSI (Pounds Per Square Inch)
- Vapor Pressure Range: 0 - 47 KPA (Kilopascals)
- Built-in back-light makes reading in dark places a cinch
- Auto shut-off timer saves battery life
- Reading HOLD Feature
- Size: 22x9x4,5cm (8 1/2" x 3 3/8" x 1 3/4")
- Weight: 312gr. (11 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty

DELMHORST EUROPE, always a step ahead in moisture measurement!