



DELMHORST
EUROPE
WHEN ACCURACY IS THE POINT.™



J-Lite moisture meter

Whether you're experienced or just starting out, you can't go wrong with the J-Lite!
With J-Lite's unique LED display, you'll be in the know no matter where the job takes you.

Your Benefits:



- 12 bright LEDs - Great for reading in direct sunlight or dark areas
- Moisture Range: 6%-30%
- Built-in calibration check
- Integral contact pins mounted on the meter prove 8mm. (5/16") penetration
- Built-in connector accepts any Delmhorst electrode
- Size: 20x8x4cm (8" x 3" x 1 5/8")
- Weight: 285gr. (10 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 3-year warranty

Available optional accessory



MCS-1

Moisture content standards are great for verifying that your Delmhorst moisture meter is in calibration.

The MCS-1 can be used on any meter with a wood scale. With two electrical resistance values (12% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.



J-Lite moisture meter

Available electrodes



26-ES Hammer electrode

Easily check high density hardwood that short pins are unable to penetrate.

It will also easily penetrate through flooring to plywood sub-floor or concrete.



2-E pin electrode

Great for hard to read areas.

Use on timber, poles and veneer.



4-E

Pin type, comes with 4 uninsulated 2497/A-100 contact pins for 8mm (5/16") penetration.

Use on kiln-dried boards up to 5cm (2") and on air-dried boards up to 32mm (5/4").



15-E Wood

Pin type, with two rows of four pins each, maximum penetration 3mm (1/8"). Penetration can be adjusted according to stock thickness by means of gauge block.

Used for veneer.



22-E

Pin type, comes with A-111 uninsulated contact pins for 38mm (1 1/2") penetration. Will also accept 496, insulated pins, 29mm (1 1/8") penetration.

For use on plaster, masonry and wood.

DELMHORST EUROPE, always a step ahead in moisture measurement!