



**DELMHORST**  
EUROPE

WHEN ACCURACY IS THE POINT.™

**TechCheck moisture meter**



**TechCheckPlus 2-in-1 meter** is designed to scan and locate moisture levels in buildings. Given the challenging conditions of building inspection, it pays to have an easy-to-use moisture meter that you can depend on. The accurate 2-in-1 TechCheck PLUS was designed with simplicity in mind and helps to make even the most demanding job simple. The newly updated TechCheck PLUS has all the great features you've come to expect, along with some new ones.

#### Your Benefits:



- Bright, clear digital display
- **Pin mode:**
  - 0.1% - 6% drywall scale, Delmhorst Exclusive
  - 6%-60% MC wood scale
  - Integral Contact pins mounted on top of meter provide 8mm (5/16") penetration
  - Built-in connector accepts any Delmhorst electrode
- **Scan Mode:** (0-300 numerical reference scale)
- Spanish language option
- Built-in back-light makes reading in dark places a cinch
- Auto-shutoff timer saves battery life
- Audible, adjustable alarm alerts you when your pre-selected MC has been reached
- Operating Temperature: from -20°C to +70°C
- Size: 22x9x4,5cm (8½"x3¾"x1¾")
- Weight: 312gr. (11 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case=
- 9V battery
- 1-year warranty

#### Special Package:

##### **TechCheck PLUS Insulation package:**

Includes meter, 21-E electrode, extra contact pins for the meter, and carrying case

[DELMHORST EUROPE, always a step ahead in moisture measurement!](#)



**Available recommended electrodes:**



**26-ES Wood**

The 496 contact pins that come with the 26-ES penetrate 29mm (1 1/8") and have insulated shanks so that only the tips are exposed. The pins make contact only at their uncoated tips and provide much more accurate readings of moisture content at various levels of penetration.

This hammer electrode will easily check high density hardwood and penetrate through flooring to plywood sub-floor or concrete.



**2-E Building materials**

Fitted with the same 8mm (5/16") penetration pins that are mounted on our pin type meters.

Electrode great for hard to read areas. Use on wood joists and drywall.



**15-E Wood**

Pin type, with two rows of four pins each, maximum penetration 3mm (1/8"). Penetration can be adjusted according to stock thickness by means of gauge block.

Used for veneer.



**22-E**

Pin type, comes with A-111 uninsulated contact pins for 38mm (1 1/2") penetration. Will also accept 496, insulated pins, 29mm (1 1/8") penetration.

For use on plaster, masonry and wood



**21-E**

Long pin type. The 608 pins that come with the 21-E are insulated, except at the tips, and can reach a maximum penetration of 8 1/4cm (3 1/4"). The 21-E is also available as 21-E/001 with 15 1/4 cm (6") penetration, or as the 21-ET with a tapped handle for hard to reach areas.

For use on roofs, insulation, or EIFS



**19-E/STC**

Features two 13cm (5") long blades, bent to a 35° angle, and coated in Teflon except for the tips.

Great for checking behind trim and baseboard molding

**Available optional accessories:**



**HP-1**

Hole punch to make pilot holes in stucco to reduce pin damage.



**MCS-1**

Moisture content standards are great for verifying that your Delmhorst moisture meter is in calibration. The MCS-1 can be used on any meter with a wood scale. With two electrical resistance values (12% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.